



KEY NO.	FOOTE PART NO.	NO. REQ'D.	DESCRIPTION	TRANSMISSION MODELS PARTS USED ON	KEY NO.	FOOTE PART NO.	NO. REQ'D.	DESCRIPTION	TRANSMISSION MODELS PARTS USED ON
1	3865	1	Housing, Upper	4360-3	37	3422	1	Spacer,	4360-3
2	1919	16	Screw, Tapping, 1/4-20x.734 Lg.	4360-3				.630x1.00x.169	
3	1151	2	Ball, Detent	4360-3	38	4286	1	Ass'y., Gear, Comb., 12 T. & 35 T.	4360-3
4	3626	2	Spring, Detent	4360-3	39	3877	1	Shaft, Idler	4360-3
5	3623	2	Screw, Set	4360-3	40	3901	1	Spacer,	4360-3
6	4336	1	Ass'y., Shifter	4360-3				.635x.875x.755	
7	3884	1	O-Ring	4360-3	41	3645	1	Sprocket, 9 T.	4360-3
8	3885	*	Washer, Plain, .505x.942x.006	4360-3	42	3853	1	Gear, Bevel, 42 T.	4360-3
8	3886	*	Washer, Plain, .505x.942x.010	4360-3	43	3749	*	Washer, Plain, .758x1.12x.010	4360-3
8	3887	*	Washer, Plain, .505x.942x.015	4360-3	43	3652	*	Washer, Plain, .758x1.12x.015	4360-3
8	3888	*	Washer, Plain, .505x.942x.020	4360-3	43	3693	*	Washer, Plain, .758x1.12x.020	4360-3
8	3889	*	Washer, Plain, .505x.942x.026	4360-3	43	3653	*	Washer, Plain, .758x1.12x.025	4360-3
8	3121	*	Washer, Plain, .505x.942x.030	4360-3	43	3408	*	Washer, Plain, .758x1.25x.020	4360-3
8	3890	*	Washer, Plain, .505x.942x.040	4360-3	43	3732	*	Washer, Plain, .758x1.25x.025	4360-3
9	1100	1	Ring, Retaining	4360-3	43	3184	*	Washer, Plain, .758x1.25x.031	4360-3
10	1099	1	Ring, Retaining	4360-3	43	3733	*	Washer, Plain, .758x1.25x.035	4360-3
11	1959	*	Washer, Plain, .632x1.00x.010	4360-3	43	3198	*	Washer, Plain, .758x1.25x.040	4360-3
11	1441	*	Washer, Plain, .632x1.00x.020	4360-3	43	3734	*	Washer, Plain, .758x1.25x.045	4360-3
11	1423	*	Washer, Plain, .632x1.00x.026	4360-3	43	3735	*	Washer, Plain, .758x1.25x.050	4360-3
11	1082	*	Washer, Plain, .632x1.00x.031	4360-3	43	3736	*	Washer, Plain, .758x1.25x.055	4360-3
11	1424	*	Washer, Plain, .632x1.00x.036	4360-3	43	3180	*	Washer, Plain, .758x1.25x.062	4360-3
11	1068	*	Washer, Plain, .632x1.00x.041	4360-3	44	3882	1	Shaft, Drive	4360-3
11	1425	*	Washer, Plain, .632x1.00x.046	4360-3	45	3646	1	Gear, Spur, 12 T.	4360-3
11	1358	*	Washer, Plain, .632x1.00x.050	4360-3	46	3707	1	Gear, Spur, 15 T.	4360-3
11	1145	*	Washer, Plain, .632x1.00x.060	4360-3	47	3866	1	Gear, Spur, 20 T.	4360-3
11	1319	*	Washer, Plain, .632x1.00x.082	4360-3	48	3719	1	Gear, Spur, 25 T.	4360-3
12	3312	1	O-Ring	4360-3	49	3868	1	Gear, Spur, 28 T.	4360-3
13	3876	2	Washer, Plain, .632x1.38x.046	4360-3	50	3683	1	Gear, Spur, 31 T.	4360-3
14	1374	1	Key, Woodruff, #9	4360-3	51	1145	1	Washer, Plain, .632x1.00x.060	4360-3
15	4134	1	Ass'y., Kit, Input Shaft	4360-3	52	3191	2	Seal, Felt	4360-3
16	3590	1	Pinion, Bevel, 14 T.	4360-3	53	3180	1	Washer, Plain, .758x1.25x.062	4360-3
17	3624	1	Ring, Retaining	4360-3	54	3880	1	Axle, L.H.	4360-3
18	3625	1	Chain, 24 Pitches	4360-3	55	3780	2	Gear, Miter, 15 T.	4360-3
19	1542	4	Bearing, Flange	4360-3	56	3656	2	Ring, Retaining	4360-3
20	3773	1	Gear, Spur, 14 T.	4360-3	57	3839	1	Gear, Spur, 32 T.	4360-3
21	3631	1	Collar, Clutch	4360-3	58	3840	1	Shaft, Cross	4360-3
22	3828	2	Key, Clutch	4360-3	59	3781	2	Gear, Miter, 15 T.	4360-3
23	1369	1	Key, Woodruff, #3	4360-3	60	3881	1	Axle, R.H.	4360-3
24	3883	1	Shaft, Intermediate	4360-3	61	3864	1	Housing, Lower	4360-3
25	1375	1	Key, Woodruff, #61	4360-3	62	4411	2	Ass'y., Kit, Puck	4360-3
26	3627	1	Ring, Retaining	4360-3	63	3276	1	Disc, Brake	4360-3
27	3830	1	Sprocket, 18 T.	4360-3	64	3758	1	Spacer	4360-3
28	3841	1	Spacer	4360-3	65	4408	1	Ass'y., Kit, Brake	4360-3
29	3786	1	Gear, Spur, 37 T.	4360-3	66	3754	3	Pin, Dowel	4360-3
30	3785	1	Gear, Spur, 35 T.	4360-3	67	4409	1	Ass'y., Kit, Anti- Rotation Bracket	4360-3
31	3867	1	Gear, Spur, 30 T.	4360-3	68	3768	1	Lever, Actuating	4360-3
32	3783	1	Gear, Spur, 25 T.	4360-3	69	3760	1	Washer, Plain, .321x1.00x.055	4360-3
33	3869	1	Gear, Spur, 22 T.	4360-3	70	3724	1	Screw, Tapping, 5/16-18x1.44 Lg.	4360-3
34	3741	1	Gear, Spur, 19 T.	4360-3	71	3847	1	Nut, Lock, 5/16-24	4360-3
35	3628	1	Washer, Plain, .640x1.37x.061	4360-3	72	4407	1	Ass'y., Kit, Screw	4360-3
36	1423	2	Washer, Plain, .632x1.00x.026	4360-3	73	3752	1	Spacer, .323x.563x1.00	4360-3
					74	4300	1	Grease	4360-3

Use in various combinations to maintain proper clearances.

**Order key #15