



IPL, Technical Specification EPA, 2002-04, 106 25 27-63

# Technical Specification EPA

<b>Spare parts</b>	Replaces	
<b>Ersatzteile</b>	Ersetzt	
<b>Pièces détachées</b>	Remplace	
<b>Reserve onderdelen</b>	Vervangt	
<b>Repuestos</b>	Reemplaza	
<b>Reservdelar</b>	Ersätter	106 25 27-62



	cu.in cc	Ø inch Ø mm	inch mm	kW rpm	rpm	rpm	rpm	NGK Champion	inch mm	type	inch mm	type	US pint liters	ml/min (8 500rpm)	US pint liters	inch	m/sec	inch	inch mm	lbs. kg	volt	
316 Electric	—	—	—	1.6 / 7 500	—	—	—	—	—	—	—	—	—	5.0 (7 500)	0.21 0.10	12"-16"	14.0	3/8"	.050 1.3	8.4 3.8	110 - 120	
335XPT	2.15 35.2	1.50 38.0	1.22 31.0	1.6 / 9 600	2 800	4 100	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO WT 582	4	0.63 0.30	3.0-7.0	0.34 0.16	12"-16"	18.3	3/8"	.050 1.3	7.5 3.4	—
136	2.22 36.3	1.50 38.0	1.26 32.0	1.6 / 9 000	3 000	4 500	4	BPMR 7 A RCI 7Y	.02 0.5	PHELON CD	.012 0.3	WALBRO WT 289	4	0.87 0.41	6.0-8.0	0.42 0.20	13"-15"	16.3	.325" / 3/8"	.050 1.3	10.1 4.6	—
141	2.44 40.2	1.57 40.0	1.26 32.0	1.9 / 9 000	3 000	4 500	4	BPMR 7 A RCI 7Y	.02 0.5	PHELON CD	.012 0.3	WALBRO WT 289	4	0.87 0.41	6.0-8.0	0.42 0.20	13"-15"	16.3	.325" / 3/8"	.050 1.3	10.1 4.6	—
340	2.49 40.8	1.57 40.0	1.28 32.5	2.0 / 9 000	2 700	3 800	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HDA 159A	4	1.06 0.50	9.0	0.53 0.25	13"-20"	17.3	.325"	.050 .058 .063 1.3 1.5 1.6	10.4 4.7	—
345	2.75 45.0	1.65 42.0	1.28 32.5	2.2 / 9 000	2 700	3 800	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HDA 159A	4	1.06 0.50	9.0	0.53 0.25	13"-20"	17.3	.325"	.050 .058 .063 1.3 1.5 1.6	10.4 4.7	—
346XP	2.75 45.0	1.65 42.0	1.28 32.5	2.5 / 9 600	2 700	3 800	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HDA 159A	4	1.06 0.50	6.0-10.0	0.59 0.28	13"-20"	18.5	.325"	.050 .058 1.3 1.5	10.6 4.8	—
350	3.01 49.4	1.73 44.0	1.28 32.5	2.3 / 9 000	2 700	3 800	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HDA 159A	4	1.06 0.50	6.0-10.0	0.53 0.25	13"-20"	17.3	.325"	.050 .058 .063 1.3 1.5 1.6	10.6 4.8	—
351	3.01 49.4	1.73 44.0	1.28 32.5	2.3 / 9 000	2 700	3 800	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HDA 159A	4	1.06 0.50	6.0-10.0	0.59 0.28	13"-20"	17.3	.325"	.050 .058 1.3 1.5	10.6 4.8	—
55 Rancher	3.25 53.2	1.81 46.0	1.26 32.0	2.5 / 9 000	2 600	3 600	4	BPMR 7 A RCI 7Y	.02 0.5	FHP ET	.012 0.3	ZAMA C1Q-EL7	4	1.27 0.60	10.0	0.63 0.30	13"-24"	17.4	.325" / 3/8"	.050 .058 1.3 1.5	11.5 5.2	—
357XP	3.50 56.5	1.81 46.0	1.34 34.0	3.2 / 9 600	2 700	3 700	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HDA 175	4	1.48 0.70	5.0-15.0	0.69 0.38	13"-24"	21.4	.325" / 3/8"	.058 1.5	12.1 5.5	—
359	3.60 59.0	1.85 47.0	1.34 34.0	2.9 / 9 000	2 700	3 700	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HDA 175	4	1.48 0.70	5.0-15.0	0.69 0.38	13"-24"	21.4	.325" / 3/8"	.058 1.5	12.1 5.5	—
261	3.75 61.5	1.89 48.0	1.34 34.0	2.9 / 9 600	2 700	3 600	4	BPMR 7 A RCI 7Y	.02 0.5	FHP ET	.012 0.3	WALBRO HDA144A	4	1.27 0.60	6.5-13.5	0.63 0.30	13"-20"	18.5	.325" / 3/8"	.050 .058 1.3 1.5	12.7 5.8	—
362XP Special	3.81 62.4	1.85 47.0	1.42 36.0	3.4 / 9 600	2 700	3 600	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HD 12B	4	1.63 0.77	4.0-20.0	0.89 0.40	13"-24"	21.4	.325" / 3/8"	.050 .058 .063 1.3 1.5 1.6	13.2 6.0	—
365 Special	3.97 65.1	1.89 48.0	1.42 36.0	3.4 / 9 300	2 700	3 600	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HD 12B	4	1.63 0.77	4.0-20.0	0.89 0.40	15"-28"	20.7	3/8"	.050 .058 .063 1.3 1.5 1.6	13.2 6.0	—
372XP	4.31 70.7	1.97 50.0	1.42 36.0	3.9 / 9 600	2 700	3 600	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO HD 12B	4	1.63 0.77	4.0-20.0	0.89 0.40	15"-28"	21.4	3/8"	.050 .058 .063 1.3 1.5 1.6	13.4 6.1	—
385XP	5.20 84.7	2.10 54.0	1.50 37.0	4.6 / 9 600	2 700	3 600	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	TILLOTSON HS 296A	4	1.90 0.90	4.0-20.0	0.90 0.50	18"-28"	21.4	3/8"	.058 1.5	15.4 7.0	—
288XP	5.31 87.0	2.13 54.0	1.50 38.0	4.5 / 9 300	2 500	3 400	4	RCI 6Y	.02 0.5	SEM CD	.012 0.3	TILLOTSON HS 283B	4	1.90 0.90	12.0-16.0 20.0-24.0	1.06 0.50	15"-32"	20.7	3/8"	.058 1.5	16.5 7.5	—
395XP	5.71 93.6	2.21 56.0	1.50 38.0	5.2 / 9 000	2 500	3 400	4	RCI 7Y	.02 0.5	SEM CD	.012 0.3	TILLOTSON HS 298A	4	1.90 0.90	14.0-21.0	1.06 0.50	18"-36"	19.6	3/8" / .404"	.050 .058 .063 1.3 1.5 1.6	17.4 7.9	—
3120XP	7.25 118.8	2.36 60.0	1.65 42.0	6.2 / 9 000	2 500	3 400	4	BPMR 7 A RCI 7Y	.02 0.5	SEM CD	.012 0.3	WALBRO WG7A	4	2.64 1.25	28.0-51.0	1.45 0.70	24"-42"	20.1	.404"	.063 1.6	22.9 10.4	—
371K	4.30 70.7	1.97 50.0	1.42 36.0	3.5 / 9 300	2 500	3 600	4	BPMR 7 A RCI 7Y	.02 0.5	FHP CD	.012 0.3	WALBRO HD 20	4	1.63 0.77	—	—	—	—	—	—	12" 20.1/9.1 14" 20.7/9.4	—
3120K	7.25 118.8	2.36 60.0	1.65 42.0	5.8 / 9 750	2 500	3 400	4	BPMR 7 A RCI 7Y	.02 0.5	FHP ET	.012 0.3	WALBRO WG 9	4	2.64 1.25	—	—	—	—	—	—	14" 29.1/13.2 16" 30.9/14.0	—