## For Husqvarna Parts Call 606-678-9623 or 606-561-4983

P.O. Box 130 Fulghum Street Hornsby, TN 38044

#### MATERIAL SAFETY DATA SHEET

#### **SECTION 1 -- IDENTIFICATION**

Product Trade Name: Husqvarna Pro Forest 30wt Bar and

Chain Oil

 Revision Date:
 02/28/02

 Phone Number:
 (731) 658-9050

 Fax Number:
 (731) 658-3591

Emergency Number: 800-424-9300 after 5:00 p.m. Chemical Family: Vegetable Oil (Rapeseed Oil)

#### SECTION 2 -- HAZARDOUS INGREDIENTS

<u>Name</u>	CAS#	App %	Regulatory Agency	<b>Exposure Limit</b>
Vegetable Oil	8001-21-6	65-90	OSHA/ACGIH	5mg/m3 Mist
Base Oil	64742-52-5	5-30	OSHA/ACGIH	5mg/m3 Mist
<b>Biodegradable Tackifier</b>	8001-21-6	2-7	OSHA/ACGIH	5mg/m3 Mist

#### **HMIS/NFPA CODES**

Health	Flammability	Reactivity	Protective Equipment
1	1	0	C, D

See Section 6, Chronic Effects, for potential over-exposure hazard.

#### **SECTION 3 -- PHYSICAL DATA**

Vapor Pressure (mmHg) at 20°C:<1 mm Hg @ 20°C</th>Specific Gravity at 60°F:.94 @ 60°FWater Solubility:SlightlyBoiling Point:Wide Range

Vapor Density (Air=1): >1 Evaporation Rate (BUAC=1): <1

Odor: Mild Hydrocarbon Odor Appearance: Amber Colored Liquid

Viscosity at 100°C CST: 10.4

#### SECTION 4 -- FIRE AND EXPLOSION HAZARDS

Flash Point: 450°F Fire Point: > 500°F

Extinguishing Media: Water Fog, Chemical Foam, Dry Chemical

Powder, CO2

Special Firefighting Procedures: Cool exposed containers with water spray.

Avoid breathing fumes.

Unusual Fire and Explosion Hazards: Pressure increase in over heated closed

containers. Cool containers with water spray.

### www.mymowerparts.com

## For Husqvarna Parts Call 606-678-9623 or 606-561-4983

#### **SECTION 5 -- REACTIVITY DATA**

**Stability:** Stable **Incompatibility:** Avoid strong oxidants. **Polymerization:** Will not occur. Partial burning produces fumes, smoke and **Thermal Decomposition:** carbon monoxide. SECTION 6 -- HEALTH HAZARD DATA Inhalation: Inhalation of fumes may result in dizziness, headache and respiratory irritation. Contact with eyes may cause minimal **Eye Contact:** irritation. **Skin Contact:** Mild irritation may occur with prolonged or repeated contact. Slightly toxic. Pulmonary aspiration hazard **Ingestion:** if vomiting occurs. 5mg/m3 as mist. ACGIH 1984-85. TLV: **Chronic Effects:** Product has a low order of acute oral toxicity. Ingredients of this product are not listed as potential carcinogens in N.T.P. Annual Report on Carcinogens, I.A.R.C. Monographs, or by O.S.H.A. HCS (g) (2) (vii). SECTION 7 -- SPECIAL PROTECTION INFORMATION Ventilation Procedure: Ventilate as needed to comply with exposure limit. **Gloves Protection:** Use impervious gloves to avoid repeated/prolonged skin contact. Use goggles/face shield to avoid eye contact. **Eye Protection:** If clothing becomes contaminated, change to Work/Hygienic Practices: fresh clean clothing. Do not wear until thoroughly laundered. SECTION 8 -- SPILL OR LEAK PROCEDURES Spill Procedures: Remove ignition sources. Recover liquid. Add absorbent to spill area. Ventilate confined spaces. Advise authorities if product enters sewers, etc. Waste Disposal: Assure conformity with applicable disposal regulations. Dispose of absorbed material at approved waste site. SECTION 9 -- SPECIAL PRECAUTIONS **Handling and Storage Precautions:** Keep containers closed when not in use. Do not handle or store near heat or flames. Use chemical resistant gloves and apron. EMERGENCY FIRST AID PROCEDURES Skin: Wash skin with soap and warm water. Wash clothing before re-use. Eye: If splashed into eyes flush eyes with clear

www.mymowerparts.com

Inhalation:

water for five (5) minutes.

immediately.

If overcome by fumes remove from exposure

# For Husqvarna Parts Call 606-678-9623 or 606-561-4983 physician.

The data presented herein is based upon tests and information, which we believe to be reliable. However, users should make their own investigations to determine the suitability of the information for their particular purpose.