

PRODUCT INFORMATION SHEET

Husqvarna AB

S-561 82 Huskvarna, Tel. no: + 46 36-14 65 00, Fax no: + 46 36-14 60 20

Date: 05.06.96

Product name: Husqvarna Bearing Lubricant.

Application: Bearing lubricant for chain saws.

The purchaser is responsible for ensuring that the product is stored, handled and used correctly, and for deciding whether it is suitable for the intended task.

This information does not include details of the risks and safety measures to be taken in the event the product is handled or used incorrectly, nor if it is mixed with another product.

This information does not take into account the unusual sensitivity of some people to products of this type.

PRODUCT INFORMATION SHEET

PRODUCT AND SAFETY PRECAUTIONS

Issued: 05.06.96
Husqvarna Bearing Lubricant

1 (3)

1. NAME OF PRODUCT AND COMPANY

Product name: Husqvarna Bearing Lubricant.

Purpose: Bearing lubricant for chain saws.

Supplier: HUSQVARNA AB
S- 561 82 Huskvarna
SWEDEN
Telephone: +46 36 14 65 00
Fax: +46 36 14 60 20

2. COMPOSITION/CLASSIFICATION OF SUBSTANCES

Highly refined mineral oil.
Lithium saponified fatty acids.

Anti-oxidation, anti-corrosion and film reinforcing additives.

3. DANGEROUS PROPERTIES

The product has been judged not harmful if handled and used as intended.
Used lubricant can contain pollutants which could result in properties harmful to health, depending on how it was previously used.

4. FIRST AID

Skin contact: Remove any soiled or splashed clothing. Wash the skin with soap and water.

If splashed in the eyes: Rinse with water. If discomfort continues, consult a doctor.

If swallowed: DO NOT INDUCE VOMITING. Prevent the lubricant from entering the respiratory passages. Consult a doctor.

PRODUCT INFORMATION SHEET

PRODUCT AND SAFETY PRECAUTIONS

Issued: 05.06.96
Husqvarna Bearing Lubricant

2 (3)

5. IN CASE OF FIRE

Classified non-flammable. If oil haze develops, it could cause a fire hazard.

Extinguishant: Powder, foam, carbonic acid.

Particular dangers: Avoid inhalation of smoke.

6. IN CASE OF SPILLAGE/ACCIDENTAL DISCHARGE

Prevent discharge into the drainage system.

7. HANDLING AND STORAGE

8. RESTRICTION TO EXPOSURE/PERSONAL SAFETY MEASURES

Hygiene: Practise good industrial hygiene.

Personal safety equipment: If long-term or repeated exposure cannot be avoided, the use of protective clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical status	Paste
Colour	Yellowish brown (42 M black)
Flashpoint	> 150 °C
Density	< 1000 kg/m ³
Soluble in organic solvent	Yes
Solubility in water	Non-soluble
Distribution coefficient	Unknown

10. STABILITY AND REACTIVITY

PRODUCT INFORMATION SHEET

PRODUCT AND SAFETY PRECAUTIONS

Issued: 05.06.96
Husqvarna Bearing Lubricant

3 (3)

11. TOXICOLOGICAL INFORMATION

Acute toxicity: The product has a low acute toxicity level when swallowed, and is not absorbed in acutely toxic quantities through the skin.
Local effects: Petroleum products have a drying effect on the skin.

12. ECOTOXICOLOGICAL INFORMATION

13. WASTE DISPOSAL

Transport to a waste disposal facility as stipulated by the authorities.

14. TRANSPORTATION INFORMATION

UN No.	Not classified
RID/ADR.	Not classified
IMO	Not classified
IATA/ICAO	Not classified
Other codes	-

15. APPLICABLE NORMS

16. OTHER INFORMATION

SUPPLIER'S NOTES:

USER'S NOTES: