



# Service Kit

## 753-04871

Date: July 13, 2004

Subject: Rear Bagger Chute Mounting Hardware for 54" Cutting Deck

Models Affected: FastAttach Triple Bag Grass Collector Model OEM-190-842

**PURPOSE:** This service kit provides the hardware for the 54" cutting deck necessary for mounting the OEM-190-842 rear bagger's discharge chute. This hardware may not have been included on your 54" cutting deck or within the OEM-190-842 Triple Bag Grass Collector accessory package. **If the right front corner lip of the 54" deck has the bracket shown in Figure 1/ Figure 3 , you do not need to install this kit.**

**NOTE:** *Save this Instruction Sheet. Refer to it when ordering replacement parts.*

### Service Kit Contents

(See Figure 1)

ITEM NO.	PART NUMBER	QTY	DESCRIPTION
1	683-0617-0637	1	BRACKET ASSEMBLY: BAGGER/CHUTE STOP (BLACK)
2	710-3168	1	BOLT: CARRIAGE: 3/8-16 x 1.00: GR1
3	712-0130	1	NUT: HEX LOCK: 3/8-16 GR8: NYLON
4	769-01324	1	THIS INSTRUCTION SHEET

#### Pre-service Preparation:

**NOTE:** *All references to left, right, front and rear of the unit are determined from the operator's position and facing the direction of forward travel.*

1. Remove the key from the ignition switch.
2. Disconnect spark plug wire(s) from the spark plug(s) and ground to engine block.
3. Fully depress the brake pedal and set the parking brake ON.
4. Allow engine and muffler to cool before proceeding.

#### Installation Instructions:

5. Raise the cutting deck to it's highest position. Locate the right front corner lip of the cutting deck.
6. Refer to Figure 2. Remove the carriage bolt and lock nut retaining the Finger Guard and Deflector Chute Stop Bracket (if so equipped). Note the orientation of the carriage bolt for re-assembly.

**NOTE:** *Save the Deflector Chute Stop and hardware if you decide to discontinue use the rear bagger. However, it is not necessary to remove the Bagger/Chute Stop Bracket when not bagging.*

7. Refer to Figure 3. Install the Bagger/Chute Stop Bracket (Item 1) on top of the deck lip using the Carriage Bolt (Item 2) and Hex Lock Nut (Item 3) supplied. Tighten securely.

8. This concludes the installation.

